

**Table E**  
**PROBABILITY OF IGNITION TABLE**

**Shading (Percent): Unshaded < 50%**

FINE DEAD FUEL MOISTURE PERCENT																
Dry Bulb Temp (F)	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
110+	100	100	80	70	60	60	50	40	40	30	30	20	20	20	20	10
100-109	100	90	80	70	60	60	50	40	40	30	30	20	20	20	10	10
90-99	100	90	80	70	60	50	40	40	30	30	30	20	20	20	10	10
80-89	100	90	80	70	60	50	40	40	30	30	20	20	20	10	10	10
70-79	100	80	70	60	60	50	40	40	30	30	20	20	20	10	10	10
60-69	90	80	70	60	50	50	40	30	30	20	20	20	20	10	10	10
50-59	90	80	70	60	50	40	40	30	30	20	20	20	10	10	10	10
40-49	90	80	70	60	50	40	40	30	30	20	20	20	10	10	10	10
30-39	80	70	60	50	50	40	30	30	20	20	20	10	10	10	10	10

**Shading (Percent): Shaded > 50%**

FINE DEAD FUEL MOISTURE PERCENT																
Dry Bulb Temp (F)	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
110+	100	90	80	70	60	50	50	40	40	30	30	20	20	20	10	10
100-109	100	90	80	70	60	50	50	40	30	30	30	20	20	20	10	10
90-99	100	90	80	70	60	50	40	40	30	30	20	20	20	10	10	10
80-89	100	80	70	60	60	50	40	40	30	30	20	20	20	10	10	10
70-79	90	80	70	60	50	50	40	30	30	30	20	20	20	10	10	10
60-69	90	80	70	60	50	40	40	30	30	20	20	20	10	10	10	10
50-59	90	80	70	60	50	40	40	30	30	20	20	20	10	10	10	10
40-49	90	80	60	50	50	40	30	30	30	20	20	20	10	10	10	10
30-39	80	80	60	50	50	40	30	30	20	20	20	10	10	10	10	10